

**In the Claims:**

The following claims have been amended as indicated below wherein added words are underlined and deleted words are indicated by ~~striketrough~~.

Please amend the claims as follows:

**1. (Currently Amended) A vitreous cutter comprising:**

a housing;

a plurality of vanes rotatably attached within the housing;

an inlet for receiving pressurized fluid causing rotation of the vanes;

an outlet for allowing the pressurized fluid to exit the cutter;

a cam attached to the vanes and rotatably attached within the housing and

structured to rotate upon rotation of the vanes; and

a vitrectomy probe contained within the housing and structured for

reciprocal movement caused by rotating the cam-;

a brake for selectively stopping rotation of the cam;

wherein the brake is structured to stop rotation of the cam in less than one (1) revolution of the cam after the pressurized fluid has been cut-off from the inlet, such that the probe is stopped in a retracted position.

2. (Cancel) The vitreous cutter of claim 1 wherein the pressurized fluid is a continuous source of air.
3. (Cancel) The vitreous cutter of claim 1 wherein the vitrectomy probe further includes:  
a cam-plate attached to a proximal end of the vitrectomy probe;  
a spring surrounding the vitrectomy probe;  
wherein the spring is positioned between the cam-plate and the housing  
such that the cam-plate is biased towards the cam; and  
wherein the cam rotation causes reciprocating movement of the vitrectomy probe.
4. (Cancel) The vitreous cutter of claim 1 further including a brake for selectively stopping rotation of the cam.
5. (Cancel) The vitreous cutter of claim 4 wherein the brake is structured to stop rotation of the cam in less than one (1) revolution of the cam after the pressurized fluid has been cut-off from the inlet.

- 6. (Currently Amended)**      The vitreous cutter of claim 41 wherein the brake further includes:
- a resilient arm fixedly attached to the housing at one end;
  - a brake-block attached to an opposing end of the arm;
  - a notched shaft-portion fixed upon an axis of rotation of the cam such that the notch receives the brake-block; and
- wherein the resilient arm is deflected by the pressurized fluid to allow rotation of the cam and where the arm causes the brake-block to be received within the notch after the pressurized fluid has been cut-off from the inlet.
- 7. (Cancel)**      The vitreous cutter of claim 1 wherein the vitreous probe further includes an aspiration bore such that the bore is in communication with an aspiration channel contained within the housing.